

Technical Data of Sealing Packing Braiding Machine

☆Type of 2 Track, 8 Spindle:

1. Size: 650X700X1600mm
2. Net weight: about 200kgs
3. Power: 380V 50Hz 0.75kw
4. Speed: 347 rotation/minute 20-30 meters/hour
5. Packing diameter Range: 3x3mm ~ 10x10mm
6. Material used for packing braiding: Sealing materials such as Asbestos, Graphite, PTFE, Carbon Fiber, Carbonized Fibre, Cotton, Ramie, etc.
7. Picture:



☆Type of 3 Track, 18 Spindle:

1. Size: 1000X1100X1800mm
2. Net weight: about 600kgs
3. Power: 380V 50Hz 0.75kw
4. Speed: 397 rotation/minute 18-28 meters/hour
5. Packing diameter Range: 5x5mm ~ 10x10mm (mix braiding 10x10mm ~ 25x25mm)
6. Material used for packing braiding: Sealing materials such as Asbestos, Graphite, PTFE, Carbon Fiber, Carbonized Fibre, Cotton, Ramie, etc.
7. Picture:



☆Type of 4 Track, 24 Spindle:

1. Size: 1300X1400X2200mm
2. Net weight: about 1200kgs
3. Power: 380V 50Hz 1.1kw
4. Speed: 200 rotation/minute 12-25 meters/hour
5. Packing diameter Range: 8x8mm ~ 16x16mm (mix braiding 16x16mm ~ 35x35mm)
6. Material used for packing braiding: Sealing materials such as Asbestos, Graphite, PTFE, Carbon Fiber, Carbonized Fibre, Cotton, Ramie, etc.
7. Picture:



☆Type of 4 Track, 32 Spindle:

1. Size: 1600X1750X2300mm
2. Net weight: about 1800kgs
3. Power: 380V 50Hz 1.5kw
4. Speed: 200 rotation/minute 12-25 meters/hour
5. Packing diameter Range: 12x12mm ~ 22x22mm (mix braiding 22x22mm ~ 50x50mm)
6. Material used for packing braiding: Sealing materials such as Asbestos, Graphite, PTFE, Carbon Fiber, Carbonized Fibre, Cotton, Ramie, etc.
7. Picture:

